

Available in : NLGI 2, 0 and 00

Product Description

Anglomoil EP Grease is a lithium 12 hydroxy lubricating grease formulated with the highest quality base oils available, and is fortified with rust and oxidation inhibitors as well as extreme pressure additives. This product has been formulated with a special additive package which insures high film strength, extreme pressure (EP) and anti-wear properties.

Typical Specifications

	NLGI 2	NLGI 0	NLGI 00
Thickener Type	Lithium	Lithium	Lithium
Thickener %	7-9	4-7	3-5
Texture	Smooth	Smooth	Smooth
Colour	Amber	Amber	Amber
Worked Penetration, ASTM D-217, @ 25°C, 60 strokes	265-295	355-385	400-430
Dropping Point ASTM D-2265 (°C)Min	177	172	-
Wheel Bearing Leakage, ASTM D-4290, gm.Loss	5	-	-
Water Washout, ASTM D-1264, % Loss Max	10	-	-
Rust Prevention, ASTM D-1743, Rating	Pass	Pass	Pass
Copper Corrosion, ASTM D-4048, Rating	1b	1b	1b
Oxidation Stability, ASTM D-942, PSI Drop	5	10	10
Oil Separation, ASTM D-1742, % Loss Max	10	-	-
Four Ball Wear, ASTM D-2266, mm Scar Dia	0.45	0.45	0.45
Four Ball EP Weld Point, ASTM D-2596, Min	250	250	250
Four Ball Load Wear Index, ASTM D-2596, Kgf.	40	40	40
Timken OK Load, ASTM D-2509, LB	45	40	45
Base Oil Characteristics: Viscosities: @ 100°C,cSt @ 40°C,cSt Viscosity Index, Min	11.5—14.5 150-200 50	15.5—17.5 180-210 80	15.5—17.5 180-210 80

PRODUCT DATA SHEET

Anglomoil Superior Lubricants

Lubricants for Automotive - Industry -Food - Farm Machinery - Marine - Earthmovers - Road Transport

2 Beaumont Rd,Mt Kuringai, NSW, Australia Phone: +61 2 9457 8566, Fax: +61 2 9457 8057 Email: info@Anglomoil.com Web: www.Anglomoil.com