



JCHEM-SD

SOLVENT DEGREASER

SPECIFICATIONS

| MEASURES | UNITS | MEASURES METHODS | GUARANTEED VALUES | |
|------------------------------|--------------------|------------------|-------------------|-----------|
| | | | MINI | MAXI |
| Density at 15 °C | kg/m ³ | ASTM D 4052 | 705 | 770 |
| Appearance | | Visual | Clair et Limpide | |
| Saybolt Colour | | ASTM D 156 | +30 | |
| Initial Point | °C | ASTM D 86 | 158 | |
| Dry Point | °C | ASTM D 86 | | 173 |
| Pensky-Martens Flash Point | °C | NFM 07019 | 42 | |
| Viscosity at 20°C | mm ² /s | ASTM D 445 | 1,20 | |
| Copper Strip Corrosion Test | | ASTM D 130 | | 1a |
| Surface Tension at 20°C | dyne/cm | de NOUY | | 25.3 |
| Dielectric Breakdown Voltage | kilovolts | ASTM D877 | | >25 |

TYPICAL VALUES

| MEASURES | UNITS | MEASURES METHODS | GUARANTEED VALUES |
|--------------------------|-----------|------------------|-------------------|
| Refractive index at 20°C | | ASTM D 1218 | 1,4150 |
| Aniline Point | °C | NFM07021 | 67 |
| Vapor Pressure at 20°C | mbar | HYSIM | <3 |
| Vapor Pressure at 37.8°C | mbar | HYSIM | <10 |
| Kauri Butanol Index | | ASTM 1133 | 28 |
| Evaporation Rate | ether = 1 | DIN 53170 | 28 |