

Product Description

Vac 10 is a Semi-Synthetic Hydraulic and Vacuum oil with boosted corrosion inhibition and moisture repellent properties for application in a range of forklift trucks.

Product Features & Benefits

Vac 10 gives:

- **Durability**, retains performance after extended use which helps to extend both oil and equipment life.
- **Hydrolytic Stability**, protects equipment from corrosion when water is present.
- **Wet and Dry Filterability**, reduces filter changes and sluggish system performance
- **Thermal and Oxidative Stability**, reduces formation of sludge and varnish thereby reducing potential downtime.
- **Demulsibility**, improved water shedding properties helping to prevent rust.
- **Rust Protection**, inhibits rust formation leading to extended equipment life and lower overall costs.
- **Low Foam**, reduced foaming tendencies reduce inadequate lubrication and potential pump damage.

Additional Information

Vac 10 meets the needs of hydraulic equipment operating under medium to severe service conditions.

Typical Characteristics

Test	Test Method	
Physical Properties		
Density @20°C	IP 160	0.839
KV @ 40°C	IP 71	10.0 cSt
KV @100°C		2.7 cSt
VI	IP 226	110

Performance Levels: Vac 10 meets or exceeds the following specifications

Denison HF-0, HF-1, HF-2	DIN 51524Part 2	AFNOR NFE 48-690 (dry)
Eaton Vickers I-286-S and M-2950-S	Sauer Danfoss	AFNOR NFE 48-691 (wet)
Cincinnati Machine P-68, P-69,P-70	Bosch Rexroth	JCMAS HK
US Steel 127 and 136	Commercial Hydraulics	
General Motors LH-03-1, LH-04-1, LH-06-1	[Except for PM-500 series silver containing pumps]	

Anglomoil Superior Lubricants

Lubricants for Automotive - Industry - Food - Farm Machinery - Marine - Earthmovers - Road Transport

2 Beaumont Rd, Mt Kuringai, NSW, Australia Phone: +61 2 9457 8566, Fax: +61 2 9457 8057 Email: info@anglomoil.com Web: www.anglomoil.com